

According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY

1.1. Identification Of The Substance/ Mixture

CEM I 52,5R White Portland Cement
CEM II-B/LL 42,5R White Portland Limestone Cement

1.2. Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against

Common white cements are used as an hydraulic binder for the production of concrete, mortars, grouts, etc.

Common cements and cement containing mixtures (hydraulic binders) are used industrially, by professionals as well as by consumers in building and construction work, indoor and outdoor. The identified uses of cements and cement containing mixtures cover the dry products and the products in a wet suspension (paste).

1.3. Company Identification

Company Name : ADANA ÇİMENTO SANAYİİ T.A.Ş

Adress : Ceyhan Yolu Üzeri 12. Km Pk:1001321Adana/TÜRKİYE

Telephone Number: +90322 3329950 E-mail of responsible person for SDS:

Burcu ATAKAY burcu.demirkiran@adanacimento.com.tr

1.4. Emergency Telephone: 114 (Poison Information Center)

+90322 3329950

2. HAZARDS IDENTIFICATION

2.1 Classification Of The Substance Or Mixture

√ Physico-Chemical Risk : Not relevant

√ Health Risk:



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

Hazard class	Hazard category	Hazard statements
Skin irritation	2	H315: Causes skin irritation
Serious eye damage/eye irritation	1	H318:Causes serious eye damage
Skin sensitisation	1B	H317: May cause an allergic skin reaction
Specific target organ toxicity single exposure respiratory tract irritation		H335: May cause respiratory irritation

√ Environment Risk : Not relevant

2.2 Label Elements

Hazard Pictograms



Signal Word: DANGER

Hazard Statements

H318 Causes serious eye damage

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

Precautionary

Statements

Wear protective gloves/protective clothing/eye protection/face

P280 protection

P264 Wash hands throughly after handling

Contaminated work clothing should not be allowed out of the

P272 workplace

IF IN EYES: Rinse cautiously with water for several minutes.

P305+P351+P338+P310 Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER or doctor/physician

IF ON SKIN: Wash with plenty of soap and water. If skin irritation

P302+P352+P333+P313 or rash occurs: Get medical advice/attention

Avoid breathing dust/fume/gas/mist/vapours/spray.

P261+P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER or

doctor/physician if you feel unwell

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents/container according to the safety data sheet

Supplemental Information:

Skin contact with wet cement, fresh concrete or mortar may cause irritation, dermatits or burns. May cause damage to products made of aluminium or other non-noble metals.

2.3.Other Hazards

The level of soluble Cr (VI) below the imposed limit of 0.0002%



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Porm No**: GBF 2015-101 **Date of Preparation**: 29.05.2015 **Revision Date/Number**: 13.06.2018/1

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

Not applicable as the product is a mixture.

3.2. Mixtures

Substance	Cas No	EC No	Concen tration(%)	Classification
Clinker	65997-15-1	266-043-4	65-100	Serious eye damage/eye irritation 1 H318 Skin irritation 2 H315 Skin sensitisation 1B H317 STOT Cat.3 H335
Limestone	1317-65-3	215-279-6	0-20	This substance is not classified as dangerous.
Gypsum	13397-24-5	603-783-2	0-5	This substance is not classified as dangerous.

4. FIRST AID MEASURES

When contacting a physician, take this SDS with you.

4.1. Description of First Aid Measures

General notes

No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet cement or wet cement containing mixtures.

Following contact with eyes

Do not rub eye as additional cornea damage is possible by mechanical stress. Remove any contact lenses and open the eyelid(s) widely to flush eye(s) immediately by thoroughly rinsing with plenty of clean water for at least 45 minutes to remove all



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

particles. If possible, use isotonic water (0,9% NaCl). Contact a specialist of occupational medicine or an eye specialist.

Following skin contact

For dry cement, remove and rinse abundantly with water.

For wet cement, wash skin with water. Remove contaminated clothing, footwear, watches, etc. And clean thoroughly before re-using them. Seek medical treatment in all cases of irritation or burns.

Following inhalation

Move the person to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops or if discomfort, coughing or other symptoms persist.

Following ingestion

Do not induce vomiting. If person is conscious, wash out mouth with water and give plenty of water to drink. Get immediate medical attention.

4.2. Most Important Symptoms And Effects, Both Acute And Delayed

Eyes: Eye contact with cement (dry or wet) may cause serious and potentially irreversible injuries.

Skin: Cement may have an irritating effect on moist skin (due to sweat or humidity) after prolonged contact or may cause contact dermatitis after repeated contact.

Prolonged skin contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt (for example when kneeling in wet concrete even when wearing trousers).

For more details see Reference (1).

Inhalation: Repeated inhalation of dust of Common cements over a long period of time increases the risk of developing lung diseases.

Environment: Under normal use, Common cement is not hazardous to the environment.



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

4.3. Indication Of Any Immediate Medical Attention And Special Treatment Needed

When contacting a physician, take this SDS with you.

5. FIRE FIGHTING MEASURES

5.1. Extinguishing Media

Cements are non-combustible and non-explosive and will not facilitate nor support combustion of other materials.

5.2.Special Hazards Arising From The Substance Or Mixture

Cements are non-combustible and non-explosive and will not facilitate or support combustion of other materials.

Cements can emit corrosive fumes.

5.3. Advice For Fire-Fighters

Cement poses no fire-related hazards. No need for special protective equipment for fire-fighters.

6. ACCIDENTAL RELEASE MEASURES

6.1.Personal Precautions, Protective Equipment And Emergency Procedures

6.1.1. For Non-Emergency Personal

Wear protective equipment as described under Section 8 and follow the advice for safe handling and use given under Section 7.

6.1.2. For Emergency Responders

Emergency procedures are not required. However, respiratory protection is needed in situations with high dust levels.

6.2. Environmental Precautions

Do not wash cement down sewage and drainage systems or into bodies of water (e.g. streams).



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

6.3. Methods And Material For Containment And Cleaning Up

Collect the spillage in a dry state if possible.

Dry cement

Use cleanup methods such as vacuum clean-upor vacuum extraction (industrial portable units, equipped with high efficiency air filters (EPA and HEPA filters, EN 1822-1:2009) or equivalent technique) which do not cause airborne dispersion. Never use compressed air.

Alternatively, wipeup the dust by mopping, wet brushing or by using water sprays or hoses (fine mist to avoid that the dust becomes airborne) and remove slurry.

If not possible, remove by slurrying with water (see wet cement).

When wet cleaning or vacuum cleaning is not possible and only dry cleaning with brushes can be done, ensure that the workers wear the appropriate personal protective equipment and prevent dust from spreading.

Avoid inhalation of cement and contact with skin. Place spilled materials into a container. Solidify before disposal as described under Section 13.

Wet cement

Clean up wet cement and place in a container. Allow material to dry and solidify before disposal as described under Section 13.

6.4. Reference To Other Sections

See sections 8 and 13 for more details.

7. HANDLING AND STORAGE

7.1. Precautions For Safe Handling

7.1.1. Protective Measures

Follow the recommendations as given under Section 8.

To clean up dry cement, see Subsection 6.3.

- Measures to prevent fire

Not applicable.



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements

Date of Preparation: 29.05.2015

Form No: GBF 2015-101

Revision Date/Number: 13.06.2018/1

Measures to prevent aerosol and dust generation

Do not sweep. Use dry cleanup methods such as vacuum clean-up or vacuum extraction, which do not cause airborne dispersion.

- Measures to protect the environment

No particular measures.

7.1.2. Information On General Occupational Hygiene

Do not handle or store near food and beverages or smoking materials.

In dusty environment, wear dust mask and protective goggles.

Use protective gloves to avoid skin contact.

7.2. Conditions For Safe Storage, Including Any Incompatibilities

Bulk cement should be stored in silos that are waterproof, dry (i.e. with internal condensation minimised), clean and protected from contamination.

Engulfment hazard: To prevent engulfment or suffocation, do not enter a confined space, such as a silo, bin, bulk truck, or other storage container or vessel that stores or contains cement without taking the proper security measures. Cement can buildup or adhere to the walls of a confined space. The cement can release, collapse or fall unexpectedly.

Packed products should be stored in unopened bags clear of the ground in cool, dry conditions and protected from excessive draught in order to avoid degradation of quality.

Bags should be stacked in a stable manner.

Do not use aluminium containers for the storage or transport of wet cement containing mixtures due to incompatibility of the materials.

7.3. Specific End Use(s)

No additional information for the specific end uses (see section 1.2).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.Control Parameters

			Conc.	Occupational Ex	posure Limits
Substance	Cas No	EC No	(%)	Long time TWA (8Hours) (mg/m3)	Long Time STEL (15Minute) (mg/m3)



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Porm No**: GBF 2015-101 **Date of Preparation**: 29.05.2015 **Revision Date/Number**: 13.06.2018/1

Clinker	65997-15-1	266-043-4	95-100	10	Total : 15 Respirable : 5
Limestone	1317-65-3	215-279-6	0-5	10	Total : 15 Respirable : 5
Gypsum	13397-24-5	603-783-2	0-5	10	Total : 15 Respirable : 5

Ref: ACGIH, OSHA

Limit Type (Country): TLV (ABD) PEL

8.2.Exposure Controls

8.2.1. Appropriate Engineering Controls

Measures to reduce generation of dust and to avoid dust propagating in the environment such as dedusting, exhaust ventilation and dry clean-up methods which do not cause airborne dispersion.

8.2.2. Individual Protection Measures Such As Personal Protection Equipment *General:*

During work avoid kneeling in fresh mortar or concrete wherever possible. If kneeling is absolutely necessary then appropriate waterproof personal protective equipment must be worn.

Do not eat, drink or smoke when working with cement to avoid contact with skin or mouth Immediately after working with cement or cement-containing materials, workers should wash or shower or use skin moisturizers.

Remove contaminated clothing, footwear, watches, etc. and clean thoroughly before re-using them.

Eye/face protection:



Wear approved glasses or safety goggles according to EN 166 when handling dry or wet cement to prevent contact with eyes.



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

Skin protection:



Use impervious, abrasion and alkali resistant gloves (made of low soluble Cr (VI) containing material), internally lined with cotton, boots, closed long-sleeved protective clothing and additionally skin care products (including barrier creams) to protect the skin from prolonged contact with wet cement. Particular care should be taken to ensure that wet cement does not enter the boots. In some circumstances such as when laying concrete or screed, waterproof trousers or kneepads are necessary.

Respiratory protection:



When a person is exposed to dust above exposure limits, use appropriate respiratory protection. It should be adapted to the dust level and conform to the relevant EN standard.

Thermal Hazards:

Not applicable.

8.2.3 Environmental Exposure Controls

Environmental exposure control for the emission of cement particles into air has to be in accordance with the available technology and regulations for the emission of general dust particles.

Air: Environmental exposure control for the emission of cement particles into air has to be in accordance with the available technology and regulations for the emission of general dust particles.

Water: Do not wash cement into sewage systems or into bodies of water, to avoid high pH. Above pH 9 negative ecotoxicological impacts are possible.

Soil and terrestrial environment: No special emission control measures are necessary for the exposure to the terrestrial environment.



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Porm No**: GBF 2015-101 **Date of Preparation**: 29.05.2015 **Revision Date/Number**: 13.06.2018/1

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information On Basic Physical And Chemical Properties

Property	Information
Appearance	Solid, inorganic material. Main particle size: 5-30 µm
Odour	Odourless
Odour threshold	No odour threshold, odourless
pH (T = 20°C in water, water-solid ratio	
1:2)	11-13.5
Melting point	> 1 250 °C
	Not applicable as under normal atmospheric conditions,
Initial boiling point and boiling range	melting point >1 250°C
Flash point	Not applicable as is not a liquid
Evaporation rate	Not applicable as is not a liquid
	Not applicable as is a solid which is non combustible and
Flammability (solid, gas)	does not cause or contribute to fire through friction
Upper/lower flammability or explosive	
limits	Not applicable as is not a flammable gas
Vapour pressure	Not applicable as melting point > 1250 °C
Vapour density	Not applicable as melting point > 1250 °C
Relative density	2.75-3.20 g/cm³
Solubility(ies) in water (T = 20 °C)	Slight (0.1-1.5 g/l)
Partition coefficient: n-octanol/water	Not applicable as is inorganic mixture
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable, as no organic peroxide present
Viscosity	Not applicable, as not a liquid
Explosive properties	Not applicable.Not explosive or pyrotechnic.
	Not applicable as does not cause or contribute to the
Oxidising properties	combustion of other materials



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

9.2. Other Information

Not applicable.

10. STABILITY AND REACTIVITY

10.1.Stability

When mixed with water, cements will harden into a stable mass that is not reactive to normal environments.

10.2. Chemical Stability

Dry cements are stable as long as they are properly stored (see Section 7) and compatible with most other building materials. They should be kept dry.

Contact with incompatible materials should be avoided.

Wet cement is alkaline and incompatible with acids, with ammonium salts, with aluminium or other non-noble metals. Cement dissolves in hydrofluoric acid to produce corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates in cementreact with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

10.3. Possibility Of Hazardous Reactions

Cements do not cause hazardous reactions.

10.4. Conditions To Avoid

Humid conditions during storage may cause lump formation and loss of product quality.

10.5. Incompatible Materials

Acids, ammonium salts, aluminium or other non-noble metals. Uncontrolled use of aluminium powder in wet cement should be avoided as hydrogen is produced.

10.6. Hazardous Decomposition Products

Cements will not decompose into any hazardous products.



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

11. TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Hazard class	Cat	Effect	Reference
Acute toxicity -	-	Limit test, rabbit, 24 hours contact, 2,000 mg/kg body weight - no	(2)
dermal		lethality.	
		Based on available data, the classification criteria are not met.	
Acute toxicity-	-	No acute toxicity by inhalation observed.	(9)
inhalation		Based on available data, the classification criteria are not met.	
Acute toxicity -	-	No indication of oral toxicity from studies with cement kiln dust.	Literature survey
oral		Based on available data, the classification criteria are not met.	
Skin corrosion/	2	Cement in contact with wet skin may cause thickening, cracking or	(2)
irritation		fissuring of the skin. Prolonged contact in combination with	Human
		abrasion may cause severe burns.	experience
Serious eye	1	Portland cement clinker caused a mixed picture of corneal effects	(10), (11)
damage/irritatio		and the calculated irritation index was 128.	
n		Common cements contain varying quantities of Portland cement	
		clinker, fly ash, blast furnace slag, gypsum, natural pozzolans, burnt	
		shale, silica fume and limestone.	
		Direct contact with cement may cause corneal damage by	
		mechanical stress, immediate or delayed irritation or inflammation.	
		Direct contact by larger amounts of dry cement or splashes of wet	
		cement may cause effects ranging from moderate eye irritation (e.g.	
		conjunctivitis or blepharitis) to chemical burns and blindness.	
Skin	1B	Some individuals may develop eczema upon exposure to wet	(4), (17)
sensitisation		cement dust, caused either by the high pH which induces irritant	
		contact dermatitis after prolonged contact.	
		The response may appear in a variety of forms ranging from a mild	
		rash to severe dermatitis and is a combination of the two above	
		mentioned mechanisms.	
Respiratory	-	There is no indication of sensitisation of the respiratory system.	(1)
sensitisation		Based on available data, the classification criteria are not met.	



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White CementsDate of Preparation: 29.05.2015Form No: GBF 2015-101Revision Date/Number: 13.06.2018/1

Hazard class	Cat	Effect	Refere	nce
Germ cell	-	No indication.	(12), (1	3)
mutagenicity		Based on available data, the classification criteria are not met.		
Carcinogenicity	-	No causal association has been established between Portland	(1)	
		cement exposure and cancer.		
		The epidemiological literature does not support the designation of		
		Portland cement as a suspected human carcinogen		
		Portland cement is not classifiable as a human carcinogen	(14)	
		(According to ACGIH A4: Agents that cause concern that they		
		could be carcinogenic for humans but which cannot be assessed		
		conclusively because of a lack of data. In vitro or animal studies do		
		not provide indications of carcinogenicity that are sufficient to		
		classify the agent with one of the other notations.).		
		Based on available data, the classification criteria are not met.		
Reproductive	-	Based on available data, the classification criteria are not met.	No	evidence
toxicity			from	human
			experie	ence
STOT-single	3	Cement dust may irritate the throat and respiratory tract. Coughing,	(1)	
exposure		sneezing, and shortness of breath may occur following exposures		
		in excess of occupational exposure limits.		
		Overall, the pattern of evidence clearly indicates that occupational		
		exposure to cement dust has produced deficits in respiratory		
		function. However, evidence available at the present time is		
		insufficient to establish with any confidence the dose-response		
		relationship for these effects.		
STOT-repeated	-	There is an indication of COPD. The effects are acute and due to	(15)	
exposure		high exposures. No chronic effects or effects at low concentration		
		have been observed.		
		Based on available data, the classification criteria are not met.		
Aspiration	-	Not applicable as cements are not used as an aerosol.		
hazard				



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

12. ECOLOGICAL INFORMATION

12.1. Toxicity

The product is not hazardous to the environment. Ecotoxicological tests with Portland cement on Daphnia magna [Reference (5)] and Selenastrum coli [Reference (6)] have shown little toxicological impact. Therefore LC50 and EC50 values could not be determined [Reference (7)]. There is no indication of sediment phase toxicity [Reference (8)]. The addition of large amounts of cement to water may, however, cause a rise in pH and may, therefore, be toxic to aquatic life under certain circumstances.

12.2. Persistence And Degradability

Not relevant. After hardening, cement presents no toxicity risks.

12.3. Bioaccumulative Potential

Not relevant. After hardening, cement presents no toxicity risks.

12.4. Mobility In Soil

Not relevant. After hardening, cement presents no toxicity risks.

12.5. Results Of PBT And vPvB Assessment

Not relevant. After hardening, cement presents no toxicity risks.

12.6. Other Adverse Effects

Not relevant.

13. DISPOSAL CONSIDERATION

13.1. Waste Treatment Methods

Do not dispose of into sewage systems or surface waters.

Product - cement that has exceeded its shelf life

EWC entry: 10 13 99 (wastes not otherwise specified)



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

Product - unused residue or dry spillage

EWC entry: 10 13 06 (Other particulates and dust)

Pick up dry unused residue or dry spillage as is. Mark the containers. Possibly reuse depending upon shelf life considerations and the requirement to avoid dust exposure. In case of disposal, harden with water and dispose according to "Product – after addition of water, hardened"

Product - slurries

Allow to harden, avoid entry in sewage and drainage systems or into bodies of water (e.g. streams) and dispose of as explained below under "Product - after addition of water, hardened".

Product - after addition of water, hardened

Dispose of according to the local legislation. Avoid entry into the sewage water system. Dispose of the hardened product as concrete waste. Due to the inertisation, concrete waste is not a dangerous waste.

EWC entries: 10 13 14 (waste from manufacturing of cement – waste concrete or concrete sludge) or 17 01 01 (construction and demolition wastes - concrete).

Packaging

Completely empty the packaging and process it according to local legislation.

EWC entry: 15 01 01 (waste paper and cardboard packaging).

14.TRANSPORT INFORMATION

Cement is not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID), therefore no classification is required.

No special precautions are needed apart from those mentioned under Section 8.



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

14.1. UN Number

Not relevant

14.2. UN Proper Shipping Name

Not relevant

14.3. Transport Hazard Class(es)

Not relevant

14.4. Packing Group

Not relevant

14.5. Environmental Hazards

Not relevant

14.6. Special Precautions For User

Not relevant

14.7. Transport In Bulk According To Annex II Of MARPOL73/78 And The IBC Code

Not relevant

15. REGULATORY INFORMATION

15.1. Safety, Health And Environmental Regulations/Legislation Specific For The Substance Or Mixture

- -Cement is a mixture according to REACH and is not subject to registration. Cement clinker is exempt from registration (Art 2.7 (b) and Annex V.10 of REACH).
- -The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds).
- The implementation of Turkish CLP [O.N. 11/12/2013-28848]



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

- The implementation of hazardous materials and mixtures safety data sheet [O.N. 13/12/2014-29204]
- -The agreement on the transport of dangerous goods by road [O.N. 24/10/2013-28801]

16. OTHER INFORMATIONS

16.1. Indications Of Changes

[O.N. 11/12/2013-28848] Regulations 2-3-15-16. Bölümlerde revizyonlar yapılmıştır.

16.2. Abbreviations And Acronyms

- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transport Association
- ADR/RID: Agreement on the transport ofdangerous goods by road/Regulations on theinternational transport of dangerous goods by rail
- LC50 Lethal Concentration where 50% of the testanimals dies.
- OEL: occupational exposure limit
- TWA: Time Weighted Averages
- CAS: Chemical Abstracts Service
- CLP: Classification, labelling and packaging (Regulation (EC) No 1272/2008)
- ECHA: European Chemicals Agency
- EINECS: European Inventory of Existing Commercial Chemical Substances
- EPA: Type of high efficiency filter
- REACH: Registiration, Evaluation and Authorisation of Chemicals
- STOT : Specific Target Organ Toxicity
- EWC: European Waste Catalogue
- vPvB : Very persistent, very bio-accumulative
- w/w : Weight by weight
 - -TWA: A Time-Weighted Average
 - -STEL: A Short Term Exposure Limit

16.3. References



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Part of Preparation**: 29.05.2015 **Porm No**: GBF 2015-101 **Date of Preparation**: 29.05.2015 **Revision Date/Number**: 13.06.2018/1

- (1) Portland Cement Dust Hazard assessment document EH75/7, UK Health and Safety Executive, 2006. Available from: http://www.hse.gov.uk/pubns/web/portlandcement.pdf.
- (2) Observations on the effects of skin irritation caused by cement, Kietzman et al, Dermatosen, 47, 5, 184-189 (1999).
- (3) European Commission's Scientific Committee on Toxicology, Ecotoxicology and the Environment (SCTEE) opinion of the risks to health from Cr (VI) in cement (European Commission, 2002).
 - http://ec.europa.eu/health/archive/ph_risk/committees/sct/documents/out158_en.pdf.
- (4) Epidemiological assessment of the occurrence of allergic dermatitis in workers in the construction industry related to the content of Cr (VI) in cement, NIOH, Page 11, 2003.
- (5) TNO report V8801/02, An acute (4-hour) inhalation toxicity study with Portland Cement Clinker CLP/GHS 03-2010-fine in rats, August 2010.
- (6) TNO report V8815/09, Evaluation of eye irritation potential of cement clinker G in vitro using the isolated chicken eye test, April 2010.
- (7) TNO report V8815/10, Evaluation of eye irritation potential of cement clinker W in vitro using the isolated chicken eye test, April 2010.
- (8) Investigation of the cytotoxic and proinflammatory effects of cement dusts in rat alveolar macrophages, Van Berlo et al, Chem. Res. Toxicol., 2009 Sept; 22(9):1548-58.
- (9) Cytotoxicity and genotoxicity of cement dusts in A549 human epithelial lung cells in vitro; Gminski et al, Abstract DGPT conference Mainz, 2008.
- (10) Comments on a recommendation from the American Conference of governmental industrial Hygienists to change the threshold limit value for Portland cement, Patrick A. Hessel and John F. Gamble, EpiLung Consulting, June 2008.
- (11) Prospective monitoring of exposure and lung function among cement workers, Interim report of the study after the data collection of Phase I-II 2006-2010, Hilde Notø, Helge Kjuus, Marit Skogstad and Karl-Christian Nordby, National Institute of Occupational Health, Oslo, Norway, March 2010.
- (12) Occurrence of allergic contact dermatitis caused by chromium in cement. A review of epidemiological investigations, Kåre Lenvik, Helge Kjuus, NIOH, Oslo, December 2011.

16.4. Classification And Procedure Used To Derive The Classification For Mixtures

Classification	Classification procedure
----------------	--------------------------



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Possible 1**Date of Preparation: 29.05.2015 **Possible 2**Revision Date/Number: 13.06.2018/1

Skin Irrit. 2, H315	on basis of test data
Eye dam. 1, H318	on basis of test data
Skin sens. 1B, H317	Human experience
STOT SE. 3, H335	Human experience

16.5. Relevant H-Phrases and P-Statements

Hazard Statements

H318 Causes serious eye damage

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation

Precautionary

Statements

Wear protective gloves/protective clothing/eye protection/face

P280 protection

P264 Wash hands throughly after handling

Contaminated work clothing should not be allowed out of the

P272 workplace

IF IN EYES: Rinse cautiously with water for several minutes.

P305+P351+P338+P310 Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER or doctor/physician

IF ON SKIN: Wash with plenty of soap and water. If skin irritation

P302+P352+P333+P313 or rash occurs: Get medical advice/attention

Avoid breathing dust/fume/gas/mist/vapours/spray.

P261+P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER or

doctor/physician if you feel unwell



According to The Regulation of Hazardous Materials and Mixtures Safety Data Sheet [O.N.13/12/2014-29204]

Product: White Cements **Date of Preparation**: 29.05.2015 **Form No**: GBF 2015-101 **Revision Date/Number**: 13.06.2018/1

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents/container according to the safety data sheet

16.6. Training Advice

In addition to health, safety and environmental training programs for their workers, companies must ensure that workers read, understand and apply the requirements of this SDS.

The information on this data sheet reflects the currently available knowledge and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product, including the use of the product in combination with any other product or any other process, is the responsibility of the user. It is implicit that the user is responsible for determining appropriate safety measures and for applying the legislation covering his own activities.

16.7. SDS Preparatory Information

Name-Surname : Burcu ATAKAY

Phone: +90 322 332 99 50/3552

Doc. No: 01.150.08